## NSN 3040-00-994-2775

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-994-2775 First End Style: External threaded **End Similarity:** Not identical Second End Style: Circular grooved and slotted **Second End Groove Width:** Between 0.0280 inches and 0.0310 inches **Second End Groove Diameter:** Between 0.2285 inches and 0.2315 inches **Overall Length:** 1.062 inches **End Application:** Eastman kodak co versamat processor model 11c-l, 11c-m, 11c-mg **Second End Slot Width:** 0.062 inches First End Diameter: Between 0.2490 inches and 0.2500 inches First End External Thread Length: 0.330 inches **Second End Distance From End To Groove:** 0.063 inches **Second End Diameter:** Between 0.2490 inches and 0.2500 inches **Second End Slot Depth:** 0.045 inches Step Quantity: **Largest Step Diameter:** 0.500 inches **Surface Finish:** 63.0 microinches **Special Features:** Chamfered 0.031 in. By 45 degrees both ends Material: Stainless steel **Material Specification:** Ek-155 mfr ref single material response

Shelf Life: N/a

**Unit Of Measure:** 

## NSN 3040-00-994-2775

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200