## NSN 3040-01-023-2799

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-023-2799

First	Fnd	Stv	le٠
ıııəı	LIIU	JLY	ıc.

Circular grooved woodruff keyway and externally threaded

First End Groove Width:

0.0615 inches

First End Groove Diameter:

0.4380 inches

**End Similarity:** 

Not identical

Second End Style:

Slotted

**Overall Length:** 

Between 7.480 inches and 7.520 inches

Second End Slot Width:

0.0600 inches

First End Distance From End To Groove:

0.4690 inches

First End Keyway Width:

Between 0.1860 inches and 0.1990 inches

First End External Keyway Length:

0.6740 inches

First End Distance From Keyway Center To End:

0.8440 inches

First End Diameter:

0.5000 inches

First End External Thread Length:

0.4690 inches

**Second End Diameter:** 

Between 0.0374 inches and 0.3750 inches

**Second End Slot Depth:** 

Between 0.0600 inches and 0.1000 inches

Step Quantity:

10

**Largest Step Diameter:** 

1.2190 inches

**Surface Finish:** 

125.0 microinches

Material:

Steel comp 1020 or steel comp 1030

**Material Specification:** 

Qq-s-633 federal specification all material responses

**Fsc Application Data:** 

Stowage rack, vehicular

## NSN 3040-01-023-2799

Shouldered Shaft - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200