NSN 3040-01-023-5666

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-023-5666 **Body Material:** Steel First End Outside Diameter: 0.625 inches **Mounting Provision:** Threaded mounting holes **Tempurature Rating:** Not rated **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Bore Diameter:** Any acceptable **Body Outside Diameter:** 2.250 inches **Overall Diameter:** 2.500 inches **Longest Horizontal Distance Between Mounting Centers:** 5.125 inches **Longest Vertical Distance Between Mounting Centers:** 0.875 inches **Mounting Facility Thread Class: Mounting Facility Thread Direction:** Right-hand First End External Thread Length: 1.531 inches **Compressed Length:** 10.625 inches **Extended Length:** 11.438 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Mounting Facility Thread Series Designator: Mounting Facility Thread Diameter:**

0.312 inches

Mounting Facility Thready Qty Per Inch (tpi):

18

Design Characteristics:

Double acting twin cylinder

NSN 3040-01-023-5666

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
First Piston Rod End Thread Diameter:
0.375 inches
First Piston Rod End Thready Qty Per Inch (tpi):
24
First Piston Rod End Thread Class:
2a
First Piston Rod End Thread Direction:
Right-hand
Piston Rod End Similarity:
Identical
Mounting Type And Location:
Flange both ends
Mounting Facility Thread Length:
0.625 inches
Port Location And Quantity:
2 center section
Port Style:
Gasket seal
Port Thread Series Designator:
Npt
Port Pipe Thread Size:
0.250 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200