## NSN 3040-01-026-3014

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-026-3014

View Online at https://aerobasegroup.com/nsn/3040-01-026-3
First End Style:
Circular grooved
First End Groove Width:
Between 0.0500 inches and 0.0540 inches
First End Groove Diameter:
0.3500 inches
End Similarity:
Not identical
Second End Style:
Splined (straight)
Overall Length:
Between 1.342 inches and 1.345 inches
First End Distance From End To Groove:
Between 0.604 inches and 0.612 inches
First End Diameter:
Between 0.3747 inches and 0.3749 inches
Second End Diameter:
Between 0.3720 inches and 0.3750 inches
Second End Spline Length:
Between 0.141 inches and 0.171 inches
Second End Spline Minor Diameter:
Between 0.2409 inches and 0.2500 inches
Second End Spline Major Diameter:
Between 0.3720 inches and 0.3750 inches
Step Quantity:
3
Second End Spline Quantity:
8
Largest Step Diameter:
Between 0.3747 inches and 0.3749 inches
Surface Finish:
16.0 microinches
Special Features:
Distance between hole centers 0.280 in. Min, 0.285 in. Max
Material:
Steel comp 4140
Material Specification:
Mil-s-5626 military specification single material response
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 3040-01-026-3014

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200

Mil-std (military Standard):

Mil-s-5626 spec.