NSN 3040-01-039-4744

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-039-4744

Steel, qq-t-825, comp 4130-canceled or steel, qq-t-825, comp 4140-canceled or steel, qq-t-825, comp 8630-canceled

Body Material: First End Outside Diameter: 2.775 inches **Mounting Provision:** Unthreaded mounting holes **Tempurature Rating:** Not rated **Bore Diameter:** Between 4.500 inches and 4.502 inches **Body Outside Diameter:** 4.937 inches **Overall Diameter:** 6.000 inches Seat Angle In Deg: 90.0 First End External Thread Length: 1.312 inches **Compressed Length:** Between 19.750 inches and 20.250 inches **Extended Length:** Between 30.000 inches and 30.500 inches **Mounting Provision Arrangement Style:** Two hole **Pressure Rating:** 4000.0 pounds per square inch **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 1.250 inches First Piston Rod End Thready Qty Per Inch (tpi): 12 First Piston Rod End Thread Class:

3a

First Piston Rod End Thread Direction:

Right-hand

Piston Rod End Similarity:

Identical

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Type And Location: Bearing both ends Mounting Facility Diameter: 1.000 inches Center To Center Distance Between Mounting Provisions: 20.250 inches **Port Location And Quantity:** 2 piston rod end Port Style: Flare Port Thread Series Designator: Nptf Port Pipe Thread Size: 0.375 inches Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A34200