

View Online at <https://aerobasegroup.com/nsn/3040-01-043-6385>

**Counterbore Diameter:**

0.3750 inches

**Counterbore Depth:**

0.6450 inches

**Outside Diameter:**

1.750 inches

**Thickness:**

0.500 inches

**Bore Diameter:**

0.4740 inches

**Plain Hole Diameter:**

0.2210 inches

**Clamp Securing Hole Style:**

Threaded

**Screw Thread Series Designator:**

Unc

**Thread Size:**

0.190 inches

**Special Features:**

Shoulder 0.720 h x 0.875 radius has 2 holes 0.190-24unc-3b 1.250 c-to-c; first hole parallel to clamp hole 0.688 c-to-c

**Material:**

Steel, qq-s-631-canceled

**Material:**

Steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1020 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 or steel comp 1060 or steel comp 1080 or steel comp 1090 or steel comp 1095

**Material Specification:**

Qq-s-631-canceled federal specification single material response

**Surface Treatment:**

Enamel

**Style Designator:**

Round, single bolt secured

**Surface Treatment:**

Enamel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A231a0