

View Online at <https://aerobasegroup.com/nsn/3040-01-043-6385>

Counterbore Diameter:

0.3750 inches

Counterbore Depth:

0.6450 inches

Outside Diameter:

1.750 inches

Thickness:

0.500 inches

Bore Diameter:

0.4740 inches

Plain Hole Diameter:

0.2210 inches

Clamp Securing Hole Style:

Threaded

Screw Thread Series Designator:

Unc

Thread Size:

0.190 inches

Special Features:

Shoulder 0.720 h x 0.875 radius has 2 holes 0.190-24unc-3b 1.250 c-to-c; first hole parallel to clamp hole 0.688 c-to-c

Material:

Steel, qq-s-631-canceled

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1020 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 or steel comp 1060 or steel comp 1080 or steel comp 1090 or steel comp 1095

Material Specification:

Qq-s-631-canceled federal specification single material response

Surface Treatment:

Enamel

Style Designator:

Round, single bolt secured

Surface Treatment:

Enamel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A231a0