## NSN 3040-01-065-6532

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-065-6532 **Body Material:** Steel, stainless **Second End Outside Diameter:** 0.312 inches **Mounting Provision:** Threaded mounting holes **Bore Diameter:** 1.062 inches **Overall Diameter:** 1.120 inches **End Application:** 6930-01-059-7085, c-130e flight trainer, a/f37a-t59 **Mounting Facility Thread Direction:** Right-hand First End Hole Diameter: 0.250 inches **Second End External Thread Length:** 0.500 inches First End Thickness At Mounting Holes: 0.380 inches **Compressed Length:** 4.620 inches **Extended Length:** 8.620 inches **Mounting Provision Arrangement Style:** Two hole **Pressure Rating:** 250.0 pounds per square inch **Mounting Facility Thread Series Designator:** Npt First End Tongue Length: 0.620 inches **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Tongue type **Piston Rod End Similarity:** 

Not identical

**Second Piston Rod End Style:** 

External threaded

## NSN 3040-01-065-6532

Linear Actuating Cylinder Assembly - Page 2 of 2



Second Piston Rod End Thread Series Designator:
Unf
Second Piston Rod End Thread Diameter:
0.312 inches
Second Piston Rod End Thready Qty Per Inch (tpi):
24
Second Piston Rod End Thread Class:
2a
Second Piston Rod End Thread Direction:
Right-hand
First End Fork Width:
0.750 inches
Err Default:
Err default
Center To Center Distance Between Mounting Provisions:
2.030 inches
Special Features:
Air return
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200