

View Online at <https://aerobasegroup.com/nsn/3040-01-073-9723>

**First End Style:**

Two circular grooves, splined and internally threaded

**First End Groove Width:**

0.1560 inches

**First End Groove Diameter:**

0.4330 inches

**End Similarity:**

Not identical

**Second End Style:**

Circular grooved, splined (straight) and externally threaded

**Second End Groove Width:**

0.1990 inches

**Second End Groove Diameter:**

0.4330 inches

**Overall Length:**

2.910 inches

**First End Distance From End To Groove:**

0.289 inches

**First End Diameter:**

0.4790 inches

**First End Spline Length:**

0.289 inches

**First End Spline Minor Diameter:**

0.4060 inches

**First End Spline Major Diameter:**

0.4790 inches

**First End Internal Thread Length:**

0.560 inches

**First End Distance Between First And Second Groove Centers:**

0.206 inches

**Second End Distance From End To Groove:**

1.990 inches

**Second End Diameter:**

0.4790 inches

**Second End Spline Length:**

1.990 inches

**Second End Spline Minor Diameter:**

0.4060 inches

**Second End Spline Major Diameter:**

0.4790 inches

**Second End Internal Thread Length:**

0.750 inches

**First End Spline Quantity:**

22

**Second End Spline Quantity:**

22

**Surface Finish:**

63.0 microinches

**Special Features:**

0.190-24unc-2b each end

**Material:**

Steel comp 4130 or steel comp 8630

**Material Specification:**

Astm a322 al 4130/8630 assn standard all material responses

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A23200