NSN 3040-01-081-6350

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-081-6350 **Body Material:** Steel First End Outside Diameter: Any acceptable **Mounting Provision:** Unthreaded mounting holes **Tempurature Rating:** 200.0 degrees fahrenheit **Bore Diameter:** 1.250 inches First End Hole Diameter: 0.307 inches First End Thickness At Mounting Holes: 0.560 inches **Compressed Length:** 6.220 inches **Extended Length:** 7.600 inches **Mounting Provision Arrangement Style:** Two hole **Pressure Rating:** 150.0 pounds per square inch **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: Bearing type **Mounting Type And Location:** Lug both ends **Mounting Facility Diameter:** 0.340 inches **Center To Center Distance Between Mounting Provisions:** 3.440 inches **Port Location And Quantity:** 1 cylinder head end Port Style: Gasket seal **Port Thread Series Designator:**

Npt

Port Pipe Thread Size:

0.125 inches

NSN 3040-01-081-6350

Linear Actuating Cylinder Assembly - Page 2 of 2



S	h	е	lf	L	if	е	:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200