

View Online at https://aerobasegroup.com/nsn/3040-01-082-1347

## **Body Material:** Steel, corrosion resisting First End Outside Diameter: 1.000 inches **Mounting Provision:** Threaded mounting holes **Tempurature Rating:** 200.0 degrees fahrenheit **Bore Diameter:** Any acceptable **Body Outside Diameter:** 4.125 inches Longest Horizontal Distance Between Mounting Centers: 3.224 inches **Longest Vertical Distance Between Mounting Centers:** 3.224 inches **Mounting Facility Thread Class:** 2b **Mounting Facility Thread Direction: Right-hand** First End External Thread Length: 1.625 inches **Compressed Length:** 7.625 inches **Extended Length:** 14.172 inches **Mounting Provision Arrangement Style:** Four hole square **Pressure Rating:** 250.0 pounds per square inch **Mounting Facility Thread Series Designator:** Unf **Mounting Facility Thread Diameter:** 0.500 inches Mounting Facility Thready Qty Per Inch (tpi): 20 **Integral Valve Operation Method:** Hydraulic or pneumatic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded

## NSN 3040-01-082-1347

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thread Series Designator: Unc First Piston Rod End Thread Diameter: 1.000 inches First Piston Rod End Thready Qty Per Inch (tpi): 8 First Piston Rod End Thread Class: 1a First Piston Rod End Thread Direction: **Right-hand** Mounting Type And Location: Flange both ends Mounting Facility Thread Length: 0.688 inches **Special Features:** Jam nut included w/standard style one rod Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A34200