

View Online at <https://aerobasegroup.com/nsn/3040-01-094-3009>

Outside Diameter:

Between 0.500 inches and 0.505 inches

Thickness:

Between 0.358 inches and 0.362 inches

Small End Diameter:

Between 0.625 inches and 0.635 inches

Bore Diameter:

1.0000 inches

Largest Diameter Length:

Between 0.298 inches and 0.302 inches

Securing Hole Quantity:

2

Angle Between Centerlines Of Securing Holes In Deg:

120.0

Screw Thread Series Designator And Location:

2nd hole unf

Securing Hole Type And Location:

Threaded-countersunk 2nd hole

Countersunk Hole Angle In Deg And Location:

110.0 2nd hole

Thread Size And Location:

0.138 inches 2nd hole

Hole Diameter And Location:

0.1060 inches 1st hole and 0.1130 inches 1st hole

Countersink Major Diameter And Location:

0.1500 inches 2nd hole and 0.1800 inches 2nd hole

Special Features:

Hex shaped large end, 0.875 inch wide across flats

Material:

Steel, qq-s-764, type 416, cond a-canceled

Material:

Steel comp 416

Material Specification:

Qq-s-764, type 416, cond a-canceled federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Round stepped

Surface Treatment:

Passivated, qq-p-35

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A231a0