

View Online at <https://aerobasegroup.com/nsn/3040-01-101-7460>

Body Material:

Any acceptable

First End Outside Diameter:

2.680 inches

Mounting Provision:

Unthreaded mounting holes

Bore Diameter:

2.120 inches

Body Outside Diameter:

2.500 inches

Overall Diameter:

2.500 inches

First End Hole Diameter:

1.000 inches

First End Thickness At Mounting Holes:

1.500 inches

Compressed Length:

24.500 inches

Extended Length:

39.500 inches

Mounting Provision Arrangement Style:

Two hole

Pressure Rating:

Between 150.0 pounds per square inch and 180.0 pounds per square inch

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

Bushing type

First End Largest Inside Diameter:

1.000 inches

Mounting Type And Location:

Fork cylinder head end

Mounting Facility Diameter:

1.000 inches

Center To Center Distance Between Mounting Provisions:

1.120 inches

Port Location And Quantity:

1 piston rod end

Port Style:

Gasket seal

Port Thread Series Designator:

Unf

Port Thread Diameter:

0.562 inches

Port Thread Qty Per Inch (tpi):

18

Port Thread Class:

2b

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A34200