

View Online at https://aerobasegroup.com/nsn/3040-01-101-7460

# **Body Material:**

Any acceptable

First End Outside Diameter:

2.680 inches

# **Mounting Provision:**

Unthreaded mounting holes

## Bore Diameter:

2.120 inches

#### **Body Outside Diameter:**

2.500 inches

#### **Overall Diameter:**

2.500 inches

First End Hole Diameter:

#### 1.000 inches

First End Thickness At Mounting Holes:

# 1.500 inches

Compressed Length:

24.500 inches

## Extended Length:

39.500 inches

# Mounting Provision Arrangement Style:

Two hole

#### Pressure Rating:

Between 150.0 pounds per square inch and 180.0 pounds per square inch

### Integral Valve Operation Method:

Hydraulic

### **Design Characteristics:**

Double acting single cylinder

### First Piston Rod End Style:

Bushing type

### First End Largest Inside Diameter:

1.000 inches

#### Mounting Type And Location:

Fork cylinder head end

### **Mounting Facility Diameter:**

1.000 inches

### Center To Center Distance Between Mounting Provisions:

1.120 inches

## **Port Location And Quantity:**

1 piston rod end

#### Port Style:

Gasket seal

Linear Actuating Cylinder Assembly - Page 2 of 2

AeroBase Group

Port Thread Series Designator: Unf Port Thread Diameter: 0.562 inches Port Thready Qty Per Inch (tpi): 18 Port Thread Class: 2b Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A34200