NSN 3040-01-106-6619

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-106-6619

View Online at https://aerobasegroup.com/nsn/3040-01-106-6619
First End Style:
Unthreaded cross drilled
End Similarity:
Not identical
Second End Style:
Woodruff keyway and cross drilled
Overall Length:
5.500 inches
First End Diameter:
Between 0.9300 inches and 0.9420 inches
First End Hole Diameter:
Between 0.1240 inches and 0.1290 inches
First End Distance From Hole Center To End:
1.298 inches
Second End Keyway Width:
Between 0.1863 inches and 0.1880 inches
Second End External Keyway Length:
0.770 inches
Second End Distance From Keyway Center To End:
0.630 inches
Second End Diameter:
0.7490 inches
Second End Hole Diameter:
Between 0.1870 inches and 0.1920 inches
Second End Distance From Hole Center To End:
0.340 inches
Second End Hole Depth:
0.7490 inches
Step Quantity:
2
Largest Step Diameter:
Between 0.930 inches and 0.942 inches
Special Features:
1st end has identical unthreaded cross drilled hole; 0.292 in center to center from 1st hole; 1st end also has slot 1.060 in length; 0.1895 in
width; 1.421 in from center of slot to end
Material:
Steel comp 1010
Material Specification:
Astm-a108 military specification single material response
Shelf Life:

--

N/a

Unit Of Measure:

NSN 3040-01-106-6619

Shouldered Shaft - Page 2 of 2



em			

No

Fiig:

A23200

Mil-std (military Standard):

spec.