## NSN 3040-01-107-6161

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-107-6161

First End Style:

Flat keyway

**End Similarity:** 

Not identical

Second End Style:

Circular grooved woodruff keyway and externally threaded

**Second End Groove Width:** 

Between 0.1240 inches and 0.1255 inches

**Second End Groove Diameter:** 

0.2700 inches

**Overall Length:** 

Between 10.055 inches and 10.115 inches

First End Keyway Width:

Between 0.1863 inches and 0.1880 inches

First End External Keyway Length:

0.750 inches

First End Keyway Depth:

Between 0.104 inches and 0.109 inches

First End Diameter:

Between 0.6240 inches and 0.6245 inches

**Second End Distance From End To Groove:** 

0.725 inches

Second End Keyway Width:

Between 0.1240 inches and 0.1255 inches

Second End External Keyway Length:

0.502 inches

Second End Distance From Keyway Center To End:

1.105 inches

**Second End Diameter:** 

Between 0.6240 inches and 0.6245 inches

Second End External Thread Length:

0.725 inches

**Step Quantity:** 

\_

**Largest Step Diameter:** 

Between 0.872 inches and 0.878 inches

Material:

Steel, cres ph13-8 mo.

**Material Specification:** 

Spec ams 5629 federal specification single material response

Shelf Life:

N/a

## NSN 3040-01-107-6161

Shouldered Shaft - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A23200