## NSN 3040-01-119-5251

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-119-5251 First End Style: Woodruff keyway **End Similarity:** Not identical **Second End Style:** Three circular grooves **Second End Groove Width:** Between 0.0390 inches and 0.0420 inches **Second End Groove Diameter:** Between 0.5280 inches and 0.5320 inches **Overall Length:** 3.812 inches First End Keyway Width: Between 0.0625 inches and 0.0635 inches First End External Keyway Length: Between 0.250 inches and 0.268 inches First End Distance From Keyway Center To End: 0.206 inches

First End Diameter:

Between 0.4330 inches and 0.4350 inches

**Second End Distance From End To Groove:** 

0.381 inches

**Second End Diameter:** 

Between 0.5605 inches and 0.5615 inches

**Second End Distance Between First And Second Groove Centers:** 

0.808 inches

Err Default:

Err default

Step Quantity:

2

**Largest Step Diameter:** 

Between 0.560 inches and 0.561 inches

**Special Features:** 

Alternate material issteel, carbon 1109 through 1119 per specification qq-s-637; second end has a connecting plate 0.937 in. Distance from end to plate, 0.125 in. Plate thk, 0.875 in. Plate w, plate has one unthd through hole 0.1245/0.1250 in. Dia, plate has two thd through holes 0.086-56 unc-2b

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1024 or steel comp 1025

**Material Specification:** 

Astm a108 assn standard all material responses

Shelf Life:

N/a

it Of Massura

## NSN 3040-01-119-5251

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200