## NSN 3040-01-121-9535

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-121-9535 First End Style: Circular grooved First End Groove Width: 0.1250 inches First End Groove Diameter: Between 1.4640 inches and 1.4710 inches **End Similarity:** Not identical **Second End Style:** Indented flat keyway **Overall Length:** 7.320 inches First End Distance From End To Groove: Between 0.156 inches and 0.159 inches First End Diameter: Between 1.5747 inches and 1.5752 inches **Second End Keyway Width:** Between 0.3750 inches and 0.3770 inches Second End External Keyway Length: Between 1.500 inches and 1.510 inches **Second End Keyway Depth:** 0.191 inches **Second End Distance From Keyway Center To End:** Between 1.190 inches and 1.195 inches Second End Diameter: Between 1.4960 inches and 1.4980 inches Step Quantity: **Largest Step Diameter:** 1.810 inches **Surface Finish:** 125.0 microinches Material: Steel **Material Specification:** Mil-s-1222, type 1, sym 87 military specification single material response Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 3040-01-121-9535

Shouldered Shaft - Page 2 of 2



Fiig:

A23200

Mil-std (military Standard):

Mil-s-1222 spec.