## NSN 3040-01-123-3013

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-123-3013

First End Style:

Two indented flat keyways

**End Similarity:** 

Not identical

Second End Style:

Two indented flat keyways

**Overall Length:** 

14.250 inches

First End Keyway Width:

Between 0.7500 inches and 0.7520 inches

First End External Keyway Length:

3.505 inches

First End Keyway Depth:

Between 0.423 inches and 0.428 inches

First End Distance From Keyway Center To End:

2.372 inches

First End Diameter:

Between 2.9930 inches and 3.0000 inches

First End Angle Between Keyways:

180.0 degrees

**Second End Keyway Width:** 

Between 0.7500 inches and 0.7520 inches

Second End External Keyway Length:

3.505 inches

**Second End Keyway Depth:** 

Between 0.423 inches and 0.428 inches

Second End Distance From Keyway Center To End:

4.117 inches

**Second End Diameter:** 

Between 3.1120 inches and 3.1140 inches

Second End Angle Between Keyways:

180.0 degrees

**Step Quantity:** 

3

**Largest Step Diameter:** 

3.620 inches

**Surface Finish:** 

63.0 microinches

Material:

Nickel alloy

**Material Specification:** 

Qq-n-286, class a federal specification single material response

## NSN 3040-01-123-3013

Shouldered Shaft - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200