

NSN 3040-01-123-5723 Shouldered Shaft - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-01-123-5723 First End Style: Two indented flat keyways **End Similarity:** Not identical Second End Style: Two indented flat keyways **Overall Length:** 14.250 inches First End Keyway Width: Between 0.7500 inches and 0.7520 inches First End External Keyway Length: 3.505 inches First End Keyway Depth: Between 0.423 inches and 0.428 inches First End Distance From Keyway Center To End: 2.372 inches First End Diameter: Between 2.9930 inches and 3.0000 inches First End Angle Between Keyways: 180.0 degrees Second End Keyway Width: Between 0.7500 inches and 0.7520 inches Second End External Keyway Length: 3.505 inches **Second End Keyway Depth:** Between 0.423 inches and 0.428 inches Second End Distance From Keyway Center To End: 4.117 inches

Second End Diameter:

Between 2.9870 inches and 2.9890 inches

Second End Angle Between Keyways:

180.0 degrees

Step Quantity:

3

Largest Step Diameter:

3.500 inches

Surface Finish:

63.0 microinches

Material:

Nickel alloy

Material Specification:

Qq-n-286, class a federal specification single material response

NSN 3040-01-123-5723

Shouldered Shaft - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200