NSN 3040-01-125-0432

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-125-0432

First End Style:

Unthreaded cross drilled

End Similarity:

Not identical

Second End Style:

Circular grooved and flat keyway

Second End Groove Width:

Between 0.0460 inches and 0.0490 inches

Second End Groove Diameter:

Between 0.7590 inches and 0.7650 inches

Overall Length:

Between 21.907 inches and 21.969 inches

First End Diameter:

Between 0.9980 inches and 1.0000 inches

First End Hole Diameter:

Between 0.3910 inches and 0.4060 inches

First End Distance From Hole Center To End:

Between 1.094 inches and 1.156 inches

Second End Distance From End To Groove:

Between 0.133 inches and 0.149 inches

Second End Keyway Width:

Between 0.1350 inches and 0.1400 inches

Second End External Keyway Length:

5.062 inches

Second End Keyway Depth:

0.221 inches

Second End Diameter:

Between 0.8110 inches and 0.8130 inches

Step Quantity:

2

Largest Step Diameter:

Between 0.998 inches and 1.000 inches

Surface Finish:

63.0 microinches

Special Features:

Second end has one additional shallow flat keyway loc on top of dp keyway, 0.188/0.189 in. Keyway w, 1.750 in. Ext keyway lg, 0.097 in.

Keyway dp

Material:

Steel comp 1035 or steel comp 1038 or steel comp 1040 or steel comp 1041 or steel comp 1042 or steel comp 1043 or steel comp 1045 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144

Material Specification:

Qq-s-633 federal specification all material responses

Shelf Life:

N/a

NSN 3040-01-125-0432

Shouldered Shaft - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A23200