NSN 3040-01-136-3108

Hydraulic Accumulator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3040-01-136-3108

| Maximum Operating Pressure: |
|--|
| 3000.000 pounds per square inch |
| Overall Length: |
| 38.000 inches |
| Overall Diameter: |
| Between 3.630 inches and 3.640 inches |
| End Application: |
| Lgm-30 |
| Maximum Fluid Volume: |
| 577.500 cubic inches |
| Separator Type: |
| Piston |
| Bleeder Opening: |
| Included |
| Port Screw Thread Diameter: |
| 0.875 inches |
| Port Screw Thready Qty Per Inch (tpi): |
| 14.000 |
| Port Screw Thread Series Designator: |
| Unf |
| Material: |
| Steel |
| Material: |
| Steel |
| Shape: |
| Cylindrical |
| Supplementary Features: |
| Ycubic capaci type 552.0 cu.In. Oil or 578.0 cu.In. Gas; burst pressure is 12000.0 psi; seal temperature range minus 40 deg. To plus 180 |
| deg. F; may bemounted in any acceptable position with end clamps; used on pump unit p/n 25-45048-24 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T164-c |
| |