NSN 3040-01-136-5036

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-136-5036

First	End	Sty	e:
-------	-----	-----	----

Externally threaded and indented flat keyway

End Similarity:

Not identical

Second End Style:

Flat keyways and internally threaded

Overall Length:

5.504 inches

End Application:

2350-01-061-2445

First End Keyway Width:

Between 0.1350 inches and 0.1450 inches

First End External Keyway Length:

0.250 inches

First End Keyway Depth:

Between 0.039 inches and 0.069 inches

First End Distance From Keyway Center To End:

1.406 inches

First End Diameter:

0.6640 inches

First End External Thread Length:

0.487 inches

Second End Keyway Width:

Between 0.1260 inches and 0.1280 inches

Second End External Keyway Length:

0.781 inches

Second End Keyway Depth:

Between 0.061 inches and 0.065 inches

Second End Diameter:

Between 0.6220 inches and 0.6280 inches

Second End Internal Thread Length:

0.620 inches

Step Quantity:

7

Largest Step Diameter:

0.875 inches

Surface Finish:

16.0 microinches

Special Features:

Stainless steel

Material:

Steel comp 303

NSN 3040-01-136-5036

Shouldered Shaft - Page 2 of 2



Material Specification

Ams 5640, type 1 assn standard single material response

Supplementary Features:

Two (2) holes, 0.030 in. dia, drilled through to id of unthreadedhole, located 1.406 in. And 3.752 in. From first end, and on opposite sides ofhole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200