## NSN 3040-01-136-5036

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-136-5036

First	End	Sty	e:
-------	-----	-----	----

Externally threaded and indented flat keyway

**End Similarity:** 

Not identical

Second End Style:

Flat keyways and internally threaded

**Overall Length:** 

5.504 inches

**End Application:** 

2350-01-061-2445

First End Keyway Width:

Between 0.1350 inches and 0.1450 inches

First End External Keyway Length:

0.250 inches

First End Keyway Depth:

Between 0.039 inches and 0.069 inches

First End Distance From Keyway Center To End:

1.406 inches

First End Diameter:

0.6640 inches

First End External Thread Length:

0.487 inches

Second End Keyway Width:

Between 0.1260 inches and 0.1280 inches

Second End External Keyway Length:

0.781 inches

**Second End Keyway Depth:** 

Between 0.061 inches and 0.065 inches

**Second End Diameter:** 

Between 0.6220 inches and 0.6280 inches

Second End Internal Thread Length:

0.620 inches

**Step Quantity:** 

7

**Largest Step Diameter:** 

0.875 inches

Surface Finish:

16.0 microinches

**Special Features:** 

Stainless steel

Material:

Steel comp 303

## NSN 3040-01-136-5036

Shouldered Shaft - Page 2 of 2



Material Specification
------------------------

Ams 5640, type 1 assn standard single material response

## **Supplementary Features:**

Two (2) holes, 0.030 in. dia, drilled through to id of unthreadedhole, located 1.406 in. And 3.752 in. From first end, and on opposite sides ofhole

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200