NSN 3040-01-148-2841



Shouldered Shaft - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-01-148-2841 First End Style: External threaded **End Similarity:** Not identical Second End Style: Circular grooved and externally threaded **Second End Groove Width:** 0.0620 inches **Second End Groove Diameter:** 0.6250 inches **Overall Length:** 32.781 inches **End Application:** Buffalo pump model 6x10 vem First End Diameter: 1.2500 inches First End External Thread Length: 0.875 inches **Second End Distance From End To Groove:** 0.562 inches **Second End Diameter:** 0.7500 inches **Second End External Thread Length:** 0.562 inches Step Quantity: 11 **Largest Step Diameter:** 2.750 inches Surface Finish: 125.0 microinches **Special Features:** Nickel-copper alloy bar class a, cold drawn; first end 1.1/4-7unc thd rh; second end 3/4-10unc thd lh; eighth step 2.368in.Dia thd-18/inch rh 13/16in.Lg; 4 key ways: 2nd step 3/8 x 0.207, 5th step 1/2 x 0.270, 8th step 5/16 x 1/8, 10th step 1/2 x 0.270; 2 tapered lengths: 4th step 2-1/4in. To 2-3/4in. By 2-17/32in. Lg, 9th step no. 9 taper 0.500in./ft for 2-7/16 in. Material: Nickel alloy **Material Specification:** Qq-n-281, class a federal specification single material response Shelf Life:

No

N/a

Unit Of Measure:

Demilitarization:

NSN 3040-01-148-2841 Shouldered Shaft - Page 2 of 2



Fiig:

A23200