NSN 3040-01-148-2841

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-148-2841

First End Style:	
External threaded	
End Similarity:	
Not identical	
Second End Style:	
Circular grooved an	d externally threaded
Second End Groov	e Width:
0.0620 inches	
Second End Groov	e Diameter:
0.6250 inches	
Overall Length:	
32.781 inches	
End Application:	
Buffalo pump mode	6x10 vem
First End Diameter	:
1.2500 inches	
First End External	Thread Length:
0.875 inches	
Second End Distar	nce From End To Groove:
0.562 inches	
Second End Diame	eter:
0.7500 inches	
Second End Extern	al Thread Length:
0.562 inches	
Step Quantity:	
11	
Largest Step Diam	eter:
2.750 inches	
Surface Finish:	
125.0 microinches	
Special Features:	
Nickel-copper alloy	bar class a, cold drawn; first end 1.1/4-7unc thd rh; second end 3/4-10unc thd lh; eighth step 2.368in.Dia thd-18/inch rh
13/16in.Lg; 4 key w	ays: 2nd step 3/8 x 0.207, 5th step 1/2 x 0.270, 8th step 5/16 x 1/8, 10th step 1/2 x 0.270; 2 tapered lengths: 4th step
2-1/4in. To 2-3/4in.	By 2-17/32in. Lg, 9th step no. 9 taper 0.500in./ft for 2-7/16 in.
Material:	
Nickel alloy	
Material Specificat	ion:
Qq-n-281, class a fe	ederal specification single material response
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	

NSN 3040-01-148-2841 Shouldered Shaft - Page 2 of 2

Fiig: A23200

