NSN 3040-01-152-5485

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-152-5485 First End Style: Two circular grooves First End Groove Width: Between 0.0290 inches and 0.0320 inches First End Groove Diameter: Between 0.2100 inches and 0.2130 inches **End Similarity:** Not identical Second End Style: Circular grooved and splined (straight) **Second End Groove Width:** 0.0250 inches **Second End Groove Diameter:** 0.2200 inches **Overall Length:** 1.660 inches **End Application:** Cai div of recon/optical inc film magazine First End Distance From End To Groove: 0.114 inches First End Diameter: Between 0.2495 inches and 0.2497 inches First End Distance Between First And Second Groove Centers: 0.569 inches **Second End Distance From End To Groove:** 0.515 inches **Second End Diameter:** Between 0.3432 inches and 0.3436 inches Second End Spline Length: 0.515 inches **Second End Spline Minor Diameter:** Between 0.2630 inches and 0.2710 inches **Second End Spline Major Diameter:** 0.3125 inches **Step Quantity:** First End Spline Quantity: 10 **Second End Spline Quantity:**

10

Largest Step Diameter:

Between 0.3432 inches and 0.3436 inches

NSN 3040-01-152-5485

Shouldered Shaft - Page 2 of 2

A23200



Surface Finish:	
16.0 microinches	
Special Features:	
0.093 in. Min, 0.098 in. Maximum diameter center	r bore through entire Ig
Material:	
Stainless steel	
Material Specification:	
Qq-s-764, class 303, condition a federal specifica	tion single material response
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	