NSN 3040-01-152-5485

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-152-5485

First End Style: Two circular grooves First End Groove Width: Between 0.0290 inches and 0.0320 inches First End Groove Diameter: Between 0.2100 inches and 0.2130 inches **End Similarity:** Not identical Second End Style: Circular grooved and splined (straight) Second End Groove Width: 0.0250 inches Second End Groove Diameter: 0.2200 inches **Overall Length:** 1.660 inches **End Application:** Cai div of recon/optical inc film magazine First End Distance From End To Groove: 0.114 inches **First End Diameter:** Between 0.2495 inches and 0.2497 inches First End Distance Between First And Second Groove Centers: 0.569 inches Second End Distance From End To Groove: 0.515 inches Second End Diameter: Between 0.3432 inches and 0.3436 inches Second End Spline Length: 0.515 inches Second End Spline Minor Diameter: Between 0.2630 inches and 0.2710 inches Second End Spline Major Diameter: 0.3125 inches **Step Quantity:** 7 First End Spline Quantity: 10 Second End Spline Quantity: 10 Largest Step Diameter:

Between 0.3432 inches and 0.3436 inches

NSN 3040-01-152-5485

Shouldered Shaft - Page 2 of 2



Surface Finish:

16.0 microinches

Special Features:

0.093 in. Min, 0.098 in. Maximum diameter center bore through entire Ig

Material:

Stainless steel

Material Specification:

Qq-s-764, class 303, condition a federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A23200