NSN 3040-01-156-5805

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-156-5805

First End Style:
Plain
End Similarity:
Not identical
Second End Style:
Splined (involute)
Overall Length:
2.675 inches
End Application:
Starter 36e153-4a, f108 engine for kc135r aircraft
First End Diameter:
Between 1.5980 inches and 1.6020 inches
Second End Diameter:
Between 1.2580 inches and 1.2620 inches
Second End Spline Length:
1.1750 inches
Second End Spline Minor Diameter:
Between 1.0950 inches and 1.1050 inches
Second End Spline Major Diameter:
Between 1.2580 inches and 1.2620 inches
Second End Pressure Angle:
20.0 degrees
Second End Pitch Diameter:
1.2000 inches
Step Quantity:
6
Second End Spline Quantity:
12
Largest Step Diameter:
Between 1.598 inches and 1.602 inches
Surface Finish:
32.0 microinches
Special Features:
Wshaft body external thd data: left hand-8 start involute thd, 1.296 pitch dia; first end bore 0.8530 - 0.8535 in. Dia, 2.390 - 2.400 in. L w/8
microinch finish; second end bore 0.437 - 0.439 in. Dia, 0.280 in. L w/16 microinch finish
Material:
Steel
Material Specification:
Ams6415 assn standard single material response
Shelf Life:

N/a

Unit Of Measure:

NSN 3040-01-156-5805

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200