NSN 3040-01-158-1567

Shouldered Shaft - Page 1 of 2

First End Style:



View Online at https://aerobasegroup.com/nsn/3040-01-158-1567

| Cross drilled and externally threaded |
|---|
| End Similarity: |
| Not identical |
| Second End Style: |
| Cross drilled hole and internally threaded |
| Overall Length: |
| 8.086 inches |
| First End Diameter: |
| 0.2500 inches |
| First End Hole Diameter: |
| Between 0.0760 inches and 0.0810 inches |
| First End Distance From Hole Center To End: |
| 0.177 inches |
| First End External Thread Length: |
| 0.800 inches |
| First End Hole Depth: |
| 0.250 inches |
| Second End Diameter: |
| 0.5900 inches |
| Second End Hole Diameter: |
| 0.0700 inches |
| Second End Distance From Hole Center To End: |
| 0.312 inches |
| Second End Hole Depth: |
| 0.502 inches |
| Second End Internal Thread Length: |
| 0.950 inches |
| Step Quantity: |
| 4 |
| Largest Step Diameter: |
| 0.590 inches |
| Surface Finish: |
| 32.0 microinches |
| Material: |
| Steel comp 17-4ph |
| Material Specification: |
| Ams-5643 assn standard single material response |
| Fsc Application Data: |
| Sensor assembly, lateral stick position |
| Shelf Life: |
| N/a |

NSN 3040-01-158-1567

Shouldered Shaft - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A23200