## NSN 3040-01-161-1341

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-161-1341

Body Material:
Steel
First End Outside Diameter:
1.375 inches
Mounting Provision:
Unthreaded mounting holes
Tempurature Rating:
-10.0 degrees fahrenheit
Overall Height:
3.000 inches
Overall Width:
3.000 inches
Bore Diameter:
2.000 inches
Longest Horizontal Distance Between Mounting Centers:
4.125 inches
Longest Vertical Distance Between Mounting Centers:
2.050 inches
First End External Thread Length:
1.625 inches
Compressed Length:
7.625 inches
Extended Length:
8.625 inches
Mounting Provision Arrangement Style:
Four hole rectangular
Pressure Rating:
3000.0 pounds per square inch
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Uns
First Piston Rod End Thread Diameter:
1.000 inches
First Piston Rod End Thready Qty Per Inch (tpi):
14
First Piston Rod End Thread Class:
29

## NSN 3040-01-161-1341

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Flange cylinder head end
Mounting Facility Diameter:
0.562 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.875 inches
Port Thready Qty Per Inch (tpi):
14
Port Thread Class:
2b
Special Features:
Viton seals; w/ piston lip seal
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200