NSN 3040-01-164-3685

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-164-3685

| First End Style: |
|-------------------------------------------------------------|
| Flat keyway |
| End Similarity: |
| Not identical |
| Second End Style: |
| Externally threaded and flat keyway |
| Overall Length: |
| 16.375 inches |
| First End Keyway Width: |
| 0.2500 inches |
| First End External Keyway Length: |
| 2.125 inches |
| First End Keyway Depth: |
| 0.125 inches |
| First End Diameter: |
| Between 0.9995 inches and 1.0000 inches |
| Second End Keyway Width: |
| 0.1880 inches |
| Second End External Keyway Length: |
| 0.406 inches |
| Second End Keyway Depth: |
| 0.094 inches |
| Second End Diameter: |
| 1.1730 inches |
| Second End External Thread Length: |
| 0.281 inches |
| Step Quantity: |
| 10 |
| Largest Step Diameter: |
| 1.875 inches |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-16782 military specification single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A23200 |
| |

NSN 3040-01-164-3685

Shouldered Shaft - Page 2 of 2

Mil-std (military Standard):

Mil-s-16782 spec.

