## NSN 3040-01-166-8294

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-166-8294 First End Style: Splined (involute) **End Similarity:** Not identical Second End Style: Circular grooved flat keyway and externally threaded **Second End Groove Width:** 0.1250 inches **Second End Groove Diameter:** 1.0620 inches **Overall Length:** 11.625 inches First End Diameter: 0.8666 inches First End Spline Length: 1.468 inches First End Spline Minor Diameter: 0.7793 inches First End Spline Major Diameter: 0.8666 inches First End Pressure Angle: 30.0 degrees First End Pitch Diameter: 0.8333 inches **Second End Distance From End To Groove:** 0.406 inches Second End Keyway Width: 0.1870 inches Second End External Keyway Length: 0.750 inches **Second End Keyway Depth:** 0.093 inches **Second End Diameter:** 1.1730 inches **Second End External Thread Length:** 0.406 inches Step Quantity: 8 First End Spline Quantity:

20

**Largest Step Diameter:** 

1.625 inches

## NSN 3040-01-166-8294

Shouldered Shaft - Page 2 of 2

Surface Finish:



8.0 microinches
Special Features:
First end circular grooved, 0.046 in. Groove w, 0.821 in. Dia, 1.391 in. Distance from end to groove; second end partial bore, 0.316 in. Dia,
1.187 in. Dp; second end internal thd, 0.937 in. Lg
Material:
Steel comp 8650
Material Specification:
Qq-s-624, type d, grade 2 federal specification single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A23200