NSN 3040-01-178-3137

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-178-3137 **Body Material:** Steel, aisi c1015 First End Outside Diameter: 1.000 inches **Tempurature Rating:** -10.0 degrees fahrenheit **Overall Height:** 4.500 inches **Overall Width:** 4.500 inches **Bore Diameter:** 3.250 inches First End External Thread Length: 1.625 inches **Compressed Length:** 18.125 inches **Extended Length:** 26.625 inches **Pressure Rating:** 3000.0 pounds per square inch **Features Provided:** Clevis pin and cushioned stroke **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 1.000 inches First Piston Rod End Thready Qty Per Inch (tpi): 14 **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand **Mounting Type And Location:**

Fork cylinder head end

Port Location And Quantity:
2 center section

NSN 3040-01-178-3137

Linear Actuating Cylinder Assembly - Page 2 of 2



| Port Style: |
|----------------------------------|
| Gasket seal |
| Port Thread Series Designator: |
| Un |
| Port Thread Diameter: |
| 1.062 inches |
| Port Thready Qty Per Inch (tpi): |
| 12 |
| Port Thread Class: |
| 2b |
| Special Features: |
| W/ piston lip seal |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |

A34200