## NSN 3040-01-182-2782

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-182-2782 **Body Material:** Steel **Mounting Provision:** Threaded mounting holes **Overall Height:** 4.500 inches **Overall Width:** 4.500 inches **Bore Diameter:** 3.250 inches **Longest Horizontal Distance Between Mounting Centers:** 1.500 inches **Longest Vertical Distance Between Mounting Centers:** 89.500 inches **Mounting Facility Thread Class: Mounting Facility Thread Direction:** Right-hand **Compressed Length:** 93.687 inches **Extended Length:** 179.687 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 5000.0 pounds per square inch **Mounting Facility Thread Series Designator:** Unc **Mounting Facility Thread Diameter:** 0.750 inches Mounting Facility Thready Qty Per Inch (tpi): **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Internal threaded First Piston Rod End Thread Series Designator:

First Piston Rod End Thread Diameter:

1.500 inches

## NSN 3040-01-182-2782

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thready Qty Per Inch (tpi):
12
First Piston Rod End Thread Class:
2b
First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Flat both ends
Mounting Facility Thread Length:
0.750 inches
Port Location And Quantity:
2 center section
Port Style:
Gasket seal
Port Thread Series Designator:
Npt
Port Pipe Thread Size:
0.750 inches
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A34200