NSN 3040-01-184-1248

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-184-1248 **Body Material:** Steel First End Outside Diameter: 2.500 inches **Mounting Provision:** Unthreaded mounting holes **Tempurature Rating:** 200.0 degrees fahrenheit **Bore Diameter:** 3.500 inches **Body Outside Diameter:** 4.000 inches **Overall Diameter:** 4.000 inches First End External Thread Length: 3.000 inches **Compressed Length:** 105.750 inches **Extended Length:** 185.250 inches **Mounting Provision Arrangement Style:** Two hole **Pressure Rating:** 1500.0 pounds per square inch **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 1.875 inches First Piston Rod End Thready Qty Per Inch (tpi): 12 **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand **Mounting Type And Location:** Tongue both ends

1.500 inches

Mounting Facility Diameter:

NSN 3040-01-184-1248

Linear Actuating Cylinder Assembly - Page 2 of 2



	т.	Cantar	Diatamaa	Daturage	Marina	Provisions:
Jenter	10	Center	Distance	between	wounting	Provisions:

102.500 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A34200