## NSN 3040-01-184-6852

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-184-6852

| First End Style:  |
|---|
| Circular grooved  |
| First End Groove Width:   |
| 0.0600 inches   |
| First End Groove Diameter:  |
| 0.5620 inches   |
| End Similarity:   |
| Not identical   |
| Second End Style:   |
| Externally threaded and flat keyway   |
| Overall Length:   |
| 11.740 inches   |
| First End Distance From End To Groove:  |
| 0.060 inches  |
| First End Diameter:   |
| 0.6880 inches   |
| Second End Keyway Width:  |
| 0.1887 inches   |
| Second End External Keyway Length:  |
| 0.520 inches  |
| Second End Keyway Depth:  |
| 0.107 inches  |
| Second End Diameter:  |
| 0.5000 inches   |
| Second End External Thread Length:  |
| 0.520 inches  |
| Step Quantity:  |
| 5   |
| Largest Step Diameter:  |
| 0.624 inches  |
| Surface Finish:   |
| 125.0 microinches   |
| Special Features:   |
| Thread relief on threaded end; through hole with diameter of 0.25in; passivate per qq-p-35; threaded 0.5-20unf-2a |
| Material:   |
| Stainless steel   |
| Material Specification:   |
| Ams 5643 17-4ph condh1150 assn standard single material response  |
| Shelf Life:   |
| N/a   |
|   |

## Unit Of Measure:

--

## NSN 3040-01-184-6852

Shouldered Shaft - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A23200

