

View Online at <https://aerobasegroup.com/nsn/3040-01-191-6223>

**Body Material:**

Steel, corrosion resisting

**First End Outside Diameter:**

0.750 inches

**Mounting Provision:**

Threaded mounting holes

**Temperature Rating:**

-10.0 degrees fahrenheit

**Overall Height:**

2.500 inches

**Overall Width:**

2.500 inches

**Bore Diameter:**

1.500 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.750 inches

**Longest Vertical Distance Between Mounting Centers:**

4.500 inches

**Mounting Facility Thread Class:**

3b

**Mounting Facility Thread Direction:**

Right-hand

**First End External Thread Length:**

0.625 inches

**Compressed Length:**

7.625 inches

**Extended Length:**

9.250 inches

**Mounting Provision Arrangement Style:**

Four hole rectangular

**Mounting Facility Thread Series Designator:**

Unc

**Mounting Facility Thread Diameter:**

0.375 inches

**Mounting Facility Thread Qty Per Inch (tpi):**

16

**Integral Valve Operation Method:**

Hydraulic

**Design Characteristics:**

Single acting single cylinder

**First Piston Rod End Style:**

External threaded

**First Piston Rod End Thread Series Designator:**

Unf

**First Piston Rod End Thread Diameter:**

0.438 inches

**First Piston Rod End Thready Qty Per Inch (tpi):**

20

**First Piston Rod End Thread Class:**

3a

**First Piston Rod End Thread Direction:**

Right-hand

**Mounting Type And Location:**

Screw both ends

**Mounting Facility Thread Length:**

0.375 inches

**Port Location And Quantity:**

1 piston rod end

**Port Style:**

Gasket seal single port

**Port Thread Series Designator:**

Unf

**Port Thread Diameter:**

0.875 inches

**Port Thready Qty Per Inch (tpi):**

14

**Port Thread Class:**

3b

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A34200