

View Online at https://aerobasegroup.com/nsn/3040-01-191-6223

### **Body Material:**

Steel, corrosion resisting

First End Outside Diameter:

0.750 inches

### **Mounting Provision:**

Threaded mounting holes

#### **Tempurature Rating:**

-10.0 degrees fahrenheit

#### **Overall Height:**

2.500 inches

**Overall Width:** 

#### 2.500 inches

### Bore Diameter:

### 1.500 inches

### Longest Horizontal Distance Between Mounting Centers:

0.750 inches

### Longest Vertical Distance Between Mounting Centers:

4.500 inches

### **Mounting Facility Thread Class:**

3b

### **Mounting Facility Thread Direction:**

**Right-hand** 

### First End External Thread Length:

0.625 inches

### **Compressed Length:**

7.625 inches

### **Extended Length:**

9.250 inches

### Mounting Provision Arrangement Style:

Four hole rectangular

### Mounting Facility Thread Series Designator:

Unc

## Mounting Facility Thread Diameter:

0.375 inches

# Mounting Facility Thready Qty Per Inch (tpi):

16

### Integral Valve Operation Method:

Hydraulic

### **Design Characteristics:**

Single acting single cylinder

### First Piston Rod End Style:

External threaded



First Piston Rod End Thread S	orios Dosignator:
Unf	enes Designator.
First Piston Rod End Thread D	iomotor.
0.438 inches	lameter:
	Other Des Inch (tri)
First Piston Rod End Thready	aty Fer inch (ipi).
20 First Piston Rod End Thread C	
	1855.
3a First Piston Rod End Thread D	izaatian
	irection:
Right-hand	
Mounting Type And Location:	
Screw both ends	46.
Mounting Facility Thread Leng	tn:
0.375 inches	
Port Location And Quantity:	
1 piston rod end	
Port Style:	
Gasket seal single port	
Port Thread Series Designator:	
Unf	
Port Thread Diameter:	
0.875 inches	
Port Thready Qty Per Inch (tpi)	:
14	
Port Thread Class:	
3b	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A34200	