NSN 3040-01-205-2092

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-205-2092

Body Material: Brass First End Outside Diameter: Between 1.250 inches and 1.251 inches **Mounting Provision:** Unthreaded mounting holes **Bore Diameter:** Between 2.625 inches and 2.627 inches **Body Outside Diameter:** 3.625 inches **Longest Horizontal Distance Between Mounting Centers:** 6.000 inches **Longest Vertical Distance Between Mounting Centers:** 5.000 inches First End External Thread Length: 1.062 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unc First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): 10 **First Piston Rod End Thread Class: First Piston Rod End Thread Direction:** Right-hand **Mounting Type And Location:** Lug both ends **Mounting Facility Diameter:** 0.625 inches **Port Location And Quantity:** 1 piston rod end

Port Style:

Gasket seal

NSN 3040-01-205-2092

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thread Series Designator:
Unf
Port Thread Diameter:
0.750 inches
Port Thready Qty Per Inch (tpi):
16
Port Thread Class:
2b
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200