NSN 3040-01-205-7534



Shouldered Shaft - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3040-01-205-7534 First End Style: External threaded **End Similarity:** Not identical Second End Style: External threaded **Overall Length:** Between 6.898 inches and 6.912 inches **End Application:** Fuel boost pump, rr54660, for f110 aircraft eng First End Diameter: Between 0.3678 inches and 0.3750 inches First End External Thread Length: Between 0.430 inches and 0.530 inches **Second End Diameter:** Between 0.9919 inches and 1.0000 inches Second End External Thread Length: 0.560 inches Step Quantity: **Largest Step Diameter:** 1.830 inches **Surface Finish:** 16.0 microinches **Special Features:** 8 first end second step 0.625-18 unjf-3a thd 0.680 in. L; second end 3.35 in. L bore 0.484 in. Diameter w/cbore 0.6325 in. Diameter cham 60 degrees 0.680 in. Dia, internal spline 13 teeth, 0.5417 in. Pitch dia, 0.500 - 0.505 in. Minor dia, 0.6167 - 0.6257 in. Major dia Material: Steel **Material Specification:** Mil-s-6709 military specification single material response Shelf Life: N/a **Unit Of Measure:** Demilitarization: Yes - demil/mli

Fiig:

A23200

Mil-std (military Standard):

Mil-s-6709 spec.