## NSN 3040-01-213-5570

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-213-5570

First End Groove Width:

Between 0.0940 inches and 0.1040 inches

First End Groove Diameter:

Between 0.1360 inches and 0.1380 inches

**End Similarity:** 

Not identical

**Overall Length:** 

Between 7.880 inches and 7.910 inches

First End Distance From End To Flat:

Between 0.340 inches and 0.350 inches

First End Distance From End To Groove:

Between 0.976 inches and 1.116 inches

First End Diameter:

Between 0.2481 inches and 0.2490 inches

First End Hole Diameter:

Between 0.1630 inches and 0.1720 inches

First End Distance From Hole Center To End:

Between 1.8120 inches and 1.8420 inches

First End Hole Depth:

Between 0.200 inches and 0.220 inches

First End Grooved Flat Length:

Between 0.2600 inches and 0.2800 inches

First End Grooved Flat Depth:

Between 0.0331 inches and 0.0340 inches

Second End Diameter:

Between 0.4991 inches and 0.4996 inches

**Second End Hole Diameter:** 

Between 0.1630 inches and 0.1720 inches

**Second End Distance From Hole Center To End:** 

3.100 inches

Second End Hole Depth:

Between 0.200 inches and 0.220 inches

**Second End Angle Between Holes:** 

57.0 degrees

Step Quantity:

2

**Largest Step Diameter:** 

Between 0.499 inches and 0.500 inches

Surface Finish:

32.0 microinches

**Special Features:** 

Both ends drilled and countersunk axially

# NSN 3040-01-213-5570

Shouldered Shaft - Page 2 of 2



М	ate	eri	al	:
	~	<b>,,,</b>	u.	-

Steel comp 347

### **Material Specification:**

Qq-s-763 federal specification single material response or ams 5646 assn standard single material response

#### Shelf Life:

N/a

#### **Unit Of Measure:**

#### Demilitarization:

Yes - demil/mli

Fiig:

A23200