## NSN 3040-01-218-9054

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-218-9054

First End Style:

Unthreaded cross drilled

**End Similarity:** 

Not identical

Second End Style:

Circular grooved, cross drilled hole, and externally threaded

**Second End Groove Width:** 

Between 0.1150 inches and 0.1300 inches

**Second End Groove Diameter:** 

Between 0.2980 inches and 0.3080 inches

**Overall Length:** 

Between 3.917 inches and 3.927 inches

First End Diameter:

Between 0.8735 inches and 0.8740 inches

First End Hole Diameter:

Between 0.2495 inches and 0.2505 inches

First End Distance From Hole Center To End:

Between 0.3570 inches and 0.3590 inches

**Second End Distance From End To Groove:** 

Between 0.7700 inches and 0.7900 inches

**Second End Diameter:** 

Between 0.3740 inches and 0.3745 inches

**Second End Hole Diameter:** 

Between 0.1060 inches and 0.1160 inches

**Second End Distance From Hole Center To End:** 

0.2870 inches

Second End External Thread Length:

Between 0.4500 inches and 0.4700 inches

Second End Hole Depth:

Between 0.3740 inches and 0.3745 inches

Step Quantity:

3

**Largest Step Diameter:** 

Between 0.9900 inches and 1.0100 inches

**Special Features:** 

First end has second hole c to c along length 1.295 in. From end, 0.2500in. Diameter porm 0.0005 in.

Material:

Steel comp 17-4ph

**Material Specification:** 

Ams5643 assn standard single material response

Shelf Life:

N/a

## NSN 3040-01-218-9054

Shouldered Shaft - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A23200