NSN 3040-01-218-9054

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-218-9054

First End Styles
First End Style: Unthreaded cross drilled
End Similarity:
Second End Style:
Circular grooved, cross drilled hole, and externally threaded Second End Groove Width:
Between 0.1150 inches and 0.1300 inches
Second End Groove Diameter:
Between 0.2980 inches and 0.3080 inches
Overall Length:
Between 3.917 inches and 3.927 inches
First End Diameter:
Between 0.8735 inches and 0.8740 inches
First End Hole Diameter:
Between 0.2495 inches and 0.2505 inches
First End Distance From Hole Center To End:
Between 0.3570 inches and 0.3590 inches
Second End Distance From End To Groove:
Between 0.7700 inches and 0.7900 inches
Second End Diameter:
Between 0.3740 inches and 0.3745 inches
Second End Hole Diameter:
Between 0.1060 inches and 0.1160 inches
Second End Distance From Hole Center To End:
0.2870 inches
Second End External Thread Length:
Between 0.4500 inches and 0.4700 inches
Second End Hole Depth:
Between 0.3740 inches and 0.3745 inches
Step Quantity:
3
Largest Step Diameter:
Between 0.9900 inches and 1.0100 inches
Special Features:
First end has second hole c to c along length 1.295 in. From end, 0.2500in. Diameter porm 0.0005 in.
Material:
Steel comp 17-4ph
Material Specification:
Ams5643 assn standard single material response
Shelf Life:
N/a

NSN 3040-01-218-9054

Shouldered Shaft - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A23200

