## NSN 3040-01-225-7026

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-225-7026

Body Material:
Steel
First End Outside Diameter:
3.500 inches all working ends
Mounting Provision:
Unthreaded mounting holes
Overall Height:
7.500 inches
Overall Width:
7.500 inches
Bore Diameter:
6.000 inches
First End External Thread Length:
3.000 inches all working ends
Compressed Length:
52.250 inches
Extended Length:
91.125 inches
Mounting Provision Arrangement Style:
Two hole
Pressure Rating:
1650.0 pounds per square inch
Features Provided:
Cushioned stroke
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
External threaded all working ends
First Piston Rod End Thread Series Designator:
Un all working ends
First Piston Rod End Thread Diameter:
1.875 inches all working ends
First Piston Rod End Thready Qty Per Inch (tpi):
12 all working ends
First Piston Rod End Thread Class:
2a all working ends
First Piston Rod End Thread Direction:
Right-hand all working ends
Mounting Type And Location:

Fork cylinder head end

## NSN 3040-01-225-7026

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Diameter:
2.250 inches
Center To Center Distance Between Mounting Provisions:
3.250 inches
Port Location And Quantity:
1 cylinder head end and 1 piston rod end
Port Style:
Gasket seal all ports
Port Thread Series Designator:
Un all ports
Port Thread Diameter:
1.625 inches all ports
Port Thready Qty Per Inch (tpi):
12 all ports
Port Thread Class:
2b all ports
Special Features:
Ports in posn 4; 4 in.Lg stop tube
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200