NSN 3040-01-225-9111

Body Material:

First End Outside Diameter: 2.000 inches all working ends

Unthreaded mounting holes

Mounting Provision:

Overall Height:

Steel

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-225-9111

5.000 inches
Overall Width:
5.000 inches
Bore Diameter:
4.000 inches
Longest Horizontal Distance Between Mounting Centers:
6.375 inches
Longest Vertical Distance Between Mounting Centers:
3.820 inches
First End External Thread Length:
2.250 inches all working ends
Compressed Length:
15.312 inches
Extended Length:
22.312 inches
Mounting Provision Arrangement Style:
Four hole rectangular
Features Provided:
Cushioned stroke
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
External threaded all working ends
First Piston Rod End Thread Series Designator:
Un all working ends
First Piston Rod End Thread Diameter:
1.750 inches all working ends
First Piston Rod End Thready Qty Per Inch (tpi):
12 all working ends
First Piston Rod End Thread Class:
2a all working ends
First Piston Rod End Thread Direction:
Right-hand all working ends

NSN 3040-01-225-9111

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Type And Location:
Flange piston rod end
Mounting Facility Diameter:
0.688 inches
Port Location And Quantity:
1 cylinder head end and 1 piston rod end
Port Style:
Gasket seal all ports
Port Thread Series Designator:
Npt all ports
Special Features:
Ports in posn 2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200