NSN 3040-01-230-3926

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-230-3926

Body Material:
Steel
First End Outside Diameter:
2.000 inches all working ends
Tempurature Rating:
-25.0 degrees fahrenheit and 165.0 degrees fahrenheit
Overall Height:
5.000 inches
Overall Width:
5.000 inches
Bore Diameter:
4.000 inches
End Application:
3920-01-143-9607
First End External Thread Length:
2.250 inches all working ends
Compressed Length:
36.500 inches
Extended Length:
63.500 inches
Pressure Rating:
3000.0 pounds per square inch
Features Provided:
Clevis pin and cushioned stroke
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
External threaded all working ends
First Piston Rod End Thread Series Designator:
Unf all working ends
First Piston Rod End Thread Diameter:
1.500 inches all working ends
First Piston Rod End Thready Qty Per Inch (tpi):
12 all working ends
First Piston Rod End Thread Class:
2a all working ends
First Piston Rod End Thread Direction:
Right-hand all working ends
Mounting Type And Location:

Fork cylinder head end

NSN 3040-01-230-3926

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Location And Quantity:
2 center section
Port Style:
Gasket seal all ports
Port Thread Series Designator:
Un all ports
Port Thread Diameter:
1.062 inches all ports
Port Thready Qty Per Inch (tpi):
12 all ports
Port Thread Class:
2b all ports
2b all ports Shelf Life:
•
Shelf Life:
Shelf Life: N/a
Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure: Demilitarization: