

View Online at https://aerobasegroup.com/nsn/3040-01-231-2975	
Body Material:	
Steel, aisi c1015	
First End Outside Diameter:	
1.375 inches all working ends	
Mounting Provision:	
Unthreaded mounting holes	
Tempurature Rating:	
-10.0 degrees fahrenheit and 165.0 degrees fahrenheit	
Overall Height:	

3.500 inches

Overall Width:

3.500 inches

Bore Diameter:

2.500 inches

Longest Horizontal Distance Between Mounting Centers:

4.875 inches

Longest Vertical Distance Between Mounting Centers:

90.375 inches

First End External Thread Length:

1.625 inches all working ends

Compressed Length:

93.812 inches

Extended Length:

180.812 inches

Mounting Provision Arrangement Style:

Four hole rectangular

Pressure Rating:

3000.0 pounds per square inch

Features Provided:

Cushioned stroke

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Single acting single cylinder

First Piston Rod End Style:

External threaded all working ends

First Piston Rod End Thread Series Designator:

Uns all working ends

First Piston Rod End Thread Diameter:

1.000 inches all working ends

First Piston Rod End Thready Qty Per Inch (tpi):

14 all working ends

NSN 3040-01-231-2975 Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thread Class:
2a all working ends
First Piston Rod End Thread Direction:
Right-hand all working ends
Mounting Facility Diameter:
0.812 inches
Port Style:
Gasket seal all ports
Port Thread Series Designator:
Unf all ports
Port Thread Diameter:
0.875 inches all ports
Port Thready Qty Per Inch (tpi):
14 all ports
Port Thread Class:
2b all ports
Special Features:
Viton seals; w/ piston lip seal
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200