## NSN 3040-01-234-8030

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-234-8030 **Body Material:** Steel First End Outside Diameter: 1.000 inches **Tempurature Rating:** -10.0 degrees fahrenheit **Overall Height:** 3.000 inches **Overall Width:** 3.000 inches **Bore Diameter:** 2.000 inches First End External Thread Length: 1.125 inches **Compressed Length:** 18.000 inches **Extended Length:** 28.000 inches **Pressure Rating:** 3000.0 pounds per square inch **Features Provided:** Clevis pin and cushioned stroke **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): 16 **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction: Mounting Type And Location:** 

Right-hand Fork cylinder head end **Port Location And Quantity:** 

1 piston rod end

## NSN 3040-01-234-8030

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.875 inches
Port Thready Qty Per Inch (tpi):
14
Port Thread Class:
2b
Special Features:
W/ pison lip seal
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200