# NSN 3040-01-239-6545

Shaft Collar - Page 1 of 2





# Chamfer Angle In Deg: 45.0 Outside Diameter: 0.875 inches

## Thickness:

0.380 inches

#### Bore Diameter:

Between 0.4990 inches and 0.5040 inches

#### Largest Diameter Length:

0.296 inches

#### End Application:

Over the horizon radar, an/fds-118

#### Securing Hole Quantity:

#### 2

### Angle Between Centerlines Of Securing Holes In Deg:

# 90.0

Screw Thread Series Designator And Location:

1st hole unc

### Securing Hole Type And Location:

Threaded 8th hole

## Screw Thready Qty Per Inch (tpi) And Location:

32 1st hole

#### **Thread Size And Location:**

0.164 inches 1st hole

#### Hole Diameter And Location:

0.1240 inches 2nd hole and 0.1290 inches 2nd hole

#### Surface Finish And Location:

125 microinches

#### Material:

Steel, qq-s-763, class 304, cond a

#### Material:

Steel comp 304

#### **Material Specification:**

Qq-s-763, class 304, cond a federal specification single material response

#### Surface Treatment:

Passivate

#### Style Designator:

Round w/double chamfer

#### Supplementary Features:

Next assembly p/n 126171 and 150116

#### Surface Treatment:

Passivated, mil-s-5002 and passivated, qq-p-35

# NSN 3040-01-239-6545

Shaft Collar - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A231a0

